

Ishida IP-Ai-P

Large Roll Label Printer
with Color Touchscreen



Ishida IP-Ai-P

Large Roll Label Printer
with Color Touchscreen



Convenient label loading

The IP-Ai-P prints at a speed of 4.7 inches per second and, with its unique batching capabilities, is ideal for high-volume printing applications in bakeries. Its custom graphics feature creates stunning labels with all required nutritional and ingredient information, and a fully customizable color touchscreen provides easy access to PLUs via category keys.

The IP-Ai-P features easy label roll front-loading with a nine-inch roll capacity to streamline prepackaging operations. For consistent and accurate pricing, the IP-Ai-P networks with ScaleLink Pro 5 and other third-party product management software.

Standard Features

- Large color touchscreen with adjustable viewing angle
- Front-loading, 9 in (230 mm) label roll capacity
- Prints all legally required ingredient and nutritional information
- Stores and prints graphics for custom labels
- Ethernet communications
- Assign images to category, presets or function keys
- 21 tactile keys
- 585 MB of memory
- Linux operating system
- ScaleLink Pro 5 communications
- Compatible with third-party communication software including Invatron's PLUM® and ADC's InterScale®

Options/Accessories

- Internal wireless communication, 802.11 b/g
- SLP-5 scale management software, including label design, data backup and remote diagnostics

Specifications

Operating Environment:	Temperature: 23-104°F (-5-40°C) Humidity: 20-85% (no condensation)
Display Unit:	12.1 in TFT color LCD with LED backlight SVGA (800 x 600)
Interface:	USB x 4 channel SD card x 1 channel
Memory Capacity:	585 MB
Communication:	Static TCP/IP 10/100 Base T Ethernet
Print Head:	3.1 in (78 mm) direct thermal (12 dot/mm)
Print Speed:	4.7 in (120 mm) per second
Label Size:	Width: 1.5-3.1 in (38-80 mm) Length: 1.2-7.9 in (30-200 mm)
Label Roll:	Inside diameter: 3.0 in (76 mm) min. Outside diameter: 9.0 in (230 mm) max.
Weight:	Main body: 42 lb (19 kg)
Power Supply:	AC110V-120V, 50/60Hz, 4 A
Power Consumption:	Stand-by: 50W In operation: 120W
Classification:	UL Listed
Warranty:	One-year limited warranty

British Columbia

12692 82nd Avenue
Surrey, British Columbia V3W 3G1
1-888-517-1556; (778) 578-2928
Fax: (778) 578-2927

ISHIDA CANADA INC.



Ontario – Quebec

2220 Argenta Rd. Unit 7
Mississauga, Ontario L5N 2K7
Ontario Phone: (647) 428-0279
Quebec Phone: 514-222-0190