

# IP-Ai

## HAND WRAPPING SYSTEM



### Premier Performance

Ishida's IP-Ai PC-based hand-wrapping system is the ideal complement to high-volume automatic wrappers. The IP-Ai is capable of fast weighing and print speeds up to 5.9 inches per second (150mm/sec). Its front-loading large, nine-inch label roll capacity keeps businesses up and running longer. Create eye-catching labels with the ability to store and print custom graphics.

Designed to enhance visibility and productivity, the large color touch screen provides easy access to PLUs via category keys. Networking capability with Ishida's ScaleLink Pro 5 and other third-party scale management software helps maintain consistent and accurate pricing.

From ergonomic design to high-speed performance, the IP-Ai offers the latest technology to streamline prepackaging operations.

#### Standard Features

- Large 12.1-in color touch screen with printer and scale base
- Front-loading, 9-in (230-mm) label roll capacity
- 3-in thermal head
- Prints all legally required safe-handling, COOL and nutritional information
- Stores and prints graphics for custom labeling
- Ethernet communications
- Adjustable touch screen viewing angle
- 19 tactile keys
- 2 GB of memory
- Over 30 selectable fixed bar code formats
- Flexible setup for ergonomic operation
- Compatible with third-party communication software, including Invatron's PLUM™ and ADC's InterScale™

#### Options and Accessories

- ScaleLink Pro 5 scale management software
- Wrap station configurations and all-purpose shelf for Scalemate, (W x D) 14 in x 34 in
- Internal RF communication



Shown with additional equipment

IP-Ai Label Drawer



#### Specifications

Weighing Capacity (Dual Range):	0-6 kg x 0.002 kg / 6-15 kg x 0.005 kg
Operating Environment:	Temperature: 23°F-104°F (-5°C-40°C) Humidity: 20-85% (no condensation)
Display Unit:	12.1-in TFT color LCD with LED backlight SVGA (800x600)
Display Items:	Tare: Four-digits Unit Price: Five-digits Weight: Five-digits
Total Price:	Six-digits
Interface:	USB x 4 channel SD card x 1 channel
Memory Capacity:	2 GB
Communication:	Static TCP/IP 10/100 Base T Ethernet DHCP
Print Head:	3in (80mm) direct thermal (12 dot/mm)
Print Speed:	Up to 5.9in (150mm) per second
Label Size:	Width: 1.5-3.1 in (38-80mm) Length: 1.2-7.9 in (30-200 mm)
Label Roll:	Inside Diameter: 3.0 in (76 mm) min. Outside Diameter: 9.0 in (230 mm) max.
Weight:	Main Body: 42lb (19kg) Scale Unit: 13 lb (6 kg)
Power Supply:	AC110 V-120 V, 50/60 Hz, 4A
Power Consumption:	Stand-by: 50 W In operation: 120 W
Classification:	NTEP CC06-029

#### Warranty

One-year limited warranty

#### Approvals



#### British Columbia

12692 82<sup>nd</sup> Avenue  
Surrey, British Columbia V3W 3G1  
1-888-517-1556; (778) 578-2928  
Fax: (778) 578-2927

#### ISHIDA CANADA INC.



#### Ontario – Quebec

2220 Argenta Rd Unit 7  
Mississauga, Ontario L5N 2K7  
Ontario Phone: (647) 428-0279  
Quebec Phone: 514-222-0190